HYDRAULIC CUTTING TOOL

general features

Dimensions mm		Weight
length	width	Weight kg
652,5	175	6,6
	5	3

STORAGE				
Туре	Dimensions mm	Weight kg	Supplied with the tool	Available upon request
VAL P7	727x202xh115	1,3	*	_

The tool features a double speed action: a fast

advancing speed for rapid approach of the blades to the cable and a slower more powerful speed for cutting.

INDUSTRIAL APPLICATION

HT-TC085

The blades are manufactured from high strength special steel, heat treated to ensure a long service life.

The head can easily be opened to allow the cutting of running cables, and can rotate through 180 degrees, to enable the operator to work in the most comfortable position.

HT-TCO851 features an automatic safety valve to bypass oil when reaching maximum pressure; a pressure release device can also be operated at any stage of operation.

INDUSTRIAL APPLICATION

HYDRAULIC CUTTING HEAD

CE

general features

Hand operated

hydraulic tool spe-

cifically designed to cut

copper, aluminium and telecommunications cables having

a max overall diameter of 85 mm.

New model, self contained, robust

and sturdy.

Max cutting Ø	Max operating pressure — bar	Dimensions mm		Weight
mm		length	width	_ Weight Kg
85	700	409	135	4,9

		STORAGE	F	
Туре	Dimensions mm	Weight kg	Supplied with the tool	Available upon request
VAL TC 085	465x155xh65	2,4	*	_



Hydraulic cutting head complete with quick automatic coupler for connection to a hydraulic pump with a working pressure of 700 bar max, (see page 128)

TCO85 features the same cutting capability as HT-TCO851.

